


IGBT Discrete

V_{CE}	650	V
I_C	60	A
$V_{CE(SAT)} I_C=60A$	1.50	V

Circuit



Applications

- Solar converters
- Uninterruptible power supplies
- Welding converters
- Mid to high range switching frequency converters

Features

- High speed smooth switching device for hard & soft switching
- Maximum junction temperature 175°C
- Positive temperature coefficient
- High ruggedness, temperature stable

Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-Emitter Breakdown Voltage	V_{CE}	650	V
DC Collector Current, limited by T_{jmax} $T_C=25^\circ C$ value limited by bondwire $T_C=100^\circ C$	I_C	80 60	A
Diode Forward Current, limited by T_{jmax} $T_C=25^\circ C$ value limited by bondwire $T_C=100^\circ C$	I_F	80 60	A
Continuous Gate-Emitter Voltage	V_{GE}	± 20	V
Transient Gate-Emitter Voltage ($t_p \leq 10\mu s, D < 0.010$)	V_{GE}	± 30	V
Turn off Safe Operating Area $V_{CE} \leq 650V$, $T_j \leq 150^\circ C$		240	A
Pulsed Collector Current, $V_{GE}=15V$, t_p limited by T_{jmax}	I_{CM}	240	A
Diode Pulsed Current, t_p limited by T_{jmax}	I_{Fpuls}	240	A
Power Dissipation, $T_j=175^\circ C$, $T_C=25^\circ C$	P_{tot}	283	W

Operating Junction Temperature	T_j	-40...+175	°C
Storage Temperature	T_s	-55...+150	°C
Soldering Temperature, wave soldering 1.6mm (0.063in.) from case for 10s		260	°C

Electrical Characteristics of the IGBT ($T_j = 25^\circ\text{C}$ unless otherwise specified):

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static						
Collector-Emitter Breakdown Voltage	BV_{CES}	$V_{GE}=0V, I_C=250\mu A$	650		-	V
Gate Threshold Voltage	$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C=0.50mA$	3.8	4.8	5.8	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$V_{GE}=15V, I_C=60A$ $T_j=25^\circ\text{C},$ $T_j=125^\circ\text{C}$ $T_j=150^\circ\text{C}$	1.20	1.50 1.70 1.80	1.80	V
Zero Gate Voltage Collector Current	I_{CES}	$V_{CE}=650V, V_{GE}=0V$ $T_j = 25^\circ\text{C},$ $T_j=150^\circ\text{C}$			0.25 3.00	mA
Gate-Emitter Leakage Current	I_{GES}	$V_{CE}= 0V, V_{GE}= \pm 20V$			100	nA

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic						
Input Capacitance	C_{ies}	$V_{CE}= 25V, V_{GE}= 0V,$ $f = 1MHz$	-	2.86	-	nF
Reverse Transfer Capacitance	C_{res}		-	0.02	-	
Gate Charge	Q_G	$V_{CC}=520V, I_C=60A,$ $V_{GE}=15V$	-	0.18	-	uC

Electrical Characteristics of the Diode (T_j= 25°C unless otherwise specified):

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static						
Diode Forward Voltage	V _F	I _F = 60A T _j = 25°C, T _j = 125°C T _j = 150°C		1.70 1.60 1.50	2.10	V

Switching Characteristic, Inductive Load





Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic , at T _j = 25℃						
Turn-on Delay Time	t _{d(on)}	V _{CC} =400V, I _C =60A, V _{GE} = -5v~15V, R _g =10Ω, Inductive Load	-	27	-	ns
Rise Time	t _r		-	41	-	ns
Turn-on Energy	E _{on}		-	2.47	-	mJ
Turn-off Delay Time	t _{d(off)}		-	81	-	ns
Fall Time	t _f		-	45	-	ns
Turn-off Energy	E _{off}		-	0.67	-	mJ
Total switching energy	E _{ts}		-	3.14	-	mJ
Dynamic , at T _j = 125℃						
Turn-on Delay Time	t _{d(on)}	V _{CC} =400V, I _C =60A, V _{GE} = -5v~15V, R _g =10Ω, Inductive Load	-	28	-	ns
Rise Time	t _r		-	49	-	ns
Turn-on Energy	E _{on}		-	2.53	-	mJ
Turn-off Delay Time	t _{d(off)}		-	88	-	ns
Fall Time	t _f		-	57	-	ns
Turn-off Energy	E _{off}		-	0.89	-	mJ
Total switching energy	E _{ts}		-	3.42	-	mJ
Dynamic , at T _j = 150℃						
Turn-on Delay Time	t _{d(on)}	V _{CC} =400V, I _C =60A, V _{GE} = -5v~15V, R _g =10Ω, Inductive Load	-	29	-	ns
Rise Time	t _r		-	52	-	ns
Turn-on Energy	E _{on}		-	2.57	-	mJ
Turn-off Delay Time	t _{d(off)}		-	93	-	ns
Fall Time	t _f		-	66	-	ns
Turn-off Energy	E _{off}		-	0.93	-	mJ
Total switching energy	E _{ts}		-	3.50	-	mJ





Electrical Characteristics of the DIODE





Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic , at T _j = 25 °C						
Reverse Recovery Current	I _{rr}	I _F =60A, V _R =400V -di/dt=460A/μs,	-	16	-	A
Reverse Recovery Charge	Q _{rr}		-	1.76	-	uC
Diode reverse recovery time	trr		-	155	-	ns
Reverse Recovery Energy	E _{rec}		-	0.34	-	mJ
Dynamic , at T _j = 125°C						
Reverse Recovery Current	I _{rr}	I _F =60A, V _R =400V -di/dt=460A/μs,	-	22	-	A
Reverse Recovery Charge	Q _{rr}		-	2.83	-	uC
Diode reverse recovery time	trr		-	196	-	ns
Reverse Recovery Energy	E _{rec}		-	0.71	-	mJ
Dynamic , at T _j = 150°C						
Reverse Recovery Current	I _{rr}	I _F =60A, V _R =400V -di/dt=460A/μs,	-	25	-	A
Reverse Recovery Charge	Q _{rr}		-	3.66	-	uC
Diode reverse recovery time	trr		-	227	-	ns
Reverse Recovery Energy	E _{rec}		-	0.85	-	mJ





Thermal Resistance




Parameter	Symbol	Max. Value	Unit
IGBT Thermal Resistance, Junction - Case	R _{th(j-c)}	0.53	K/W
Diode Thermal Resistance, Junction - Case	R _{th(j-c)}	1.05	K/W
Thermal Resistance, Junction - Ambient	R _{th(j-a)}	40	K/W












● Circuit Diagram




● Package Outline Information



TO-247AB		
Dim	Min	Max
A	4.80	5.20
A1	2.21	2.61
A2	1.85	2.15
b	1.0	1.4
b2	1.91	2.21
C	0.5	0.7
D	20.70	21.30
D1	16.25	16.85
E	15.50	16.10
E1	13.0	13.6
E2	4.80	5.20
E3	2.30	2.70
L	19.62	20.22
L1	-	4.30
Φ P	3.40	3.80
Φ P1	-	7.30
S	6.15TYP	
H1	5.44TYP	
b3	2.80	3.20


ISSUE	REVISION	DATE
1.0	Add Datasheet	19-Oct-23

Marking Information



Package Parameters

Base Part Number	Package Type	Standard Pack		Orderable Part Number
		Form	Quantity	
DGW60N65CTS2A	TO-247	Tube	30	DGW60N65CTS2A



Disclaimer

The information presented in this document is for reference only. This publication is made by Shanghai Sunco Electronics Co., Ltd. , our company reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The data provided in this specification comes from professional testing equipment of Russiansunco Electronic Laboratory, not general testing equipment. All the data is exclusively intended for technically trained staff. You and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

IGBTs is the device which is sensitive to the static electricity, it is necessary to protect the device from being damaged by the static electricity when using it.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.