

## IGBT Modules



$V_{CES}$  1200V  
 $I_C$  450A


## Applications

- Motion/sevo control
- High frequency switching application
- UPS (Uninterruptible Power Supplies)
- Welding machine

## Features

- Low  $V_{CE(sat)}$  with trench technology
- Low switching losses especially  $E_{off}$
- $V_{CE(sat)}$  with positive temperature coefficient
- High short circuit capability(10us)
- Including ultra fast & soft recovery anti-parallel FWD
- Low inductance package
- Maximum junction temperature 175°C

**Circuit**



## ● IGBT

### Absolute Maximum Ratings

| Parameter                         | Symbol    | Conditions                                     | Value    | Unit |
|-----------------------------------|-----------|------------------------------------------------|----------|------|
| Collector-Emitter Voltage         | $V_{CES}$ | $V_{GE}=0V$ , $I_C=1mA$ , $T_{vj}=25^{\circ}C$ | 1200     | V    |
| Continuous Collector Current      | $I_C$     | $T_C=100^{\circ}C$                             | 450      | A    |
| Repetitive Peak Collector Current | $I_{CRM}$ | $t_p=1ms$                                      | 900      | A    |
| Gate-Emitter Voltage              | $V_{GES}$ | $T_{vj}=25^{\circ}C$                           | $\pm 20$ | V    |
| Total Power Dissipation           | $P_{tot}$ | $T_C=25^{\circ}C$<br>$T_{vjmax}=175^{\circ}C$  | 2300     | W    |

## Characteristic Values

| Parameter                               | Symbol        | Conditions                                                                                  | Value |      |      | Unit     |
|-----------------------------------------|---------------|---------------------------------------------------------------------------------------------|-------|------|------|----------|
|                                         |               |                                                                                             | Min.  | Typ. | Max. |          |
| Gate-emitter Threshold Voltage          | $V_{GE(th)}$  | $V_{GE}=V_{CE}, I_C=12mA, T_{vj}=25^{\circ}C$                                               | 5.2   | 5.8  | 6.4  | V        |
| Collector-Emitter Cut-off Current       | $I_{CES}$     | $V_{CE}=1200V, V_{GE}=0V, T_{vj}=25^{\circ}C$                                               |       |      | 1.0  | mA       |
| Collector-Emitter Saturation Voltage    | $V_{CE(sat)}$ | $I_C=450A, V_{GE}=15V, T_{vj}=25^{\circ}C$                                                  |       | 1.85 | 2.20 | V        |
|                                         |               | $I_C=450A, V_{GE}=15V, T_{vj}=125^{\circ}C$                                                 |       | 2.15 |      |          |
|                                         |               | $I_C=450A, V_{GE}=15V, T_{vj}=150^{\circ}C$                                                 |       | 2.25 |      |          |
| Gate Charge                             | $Q_G$         |                                                                                             |       | 3.50 |      | uC       |
| Internal Gate Resistance                | $R_{Gint}$    |                                                                                             |       | 1.67 |      | $\Omega$ |
| Input Capacitance                       | $C_{ies}$     | $V_{CE}=25V, V_{GE}=0V, f=1MHz, T_{vj}=25^{\circ}C$                                         |       | 45.9 |      | nF       |
| Reverse Transfer Capacitance            | $C_{res}$     |                                                                                             |       | 1.10 |      | nF       |
| Gate-Emitter leakage current            | $I_{GES}$     | $V_{CE}=0V, V_{GE}=20V, T_{vj}=25^{\circ}C$                                                 |       |      | 400  | nA       |
| Turn-on Delay Time                      | $t_{d(on)}$   | $I_C=450A$<br>$V_{CE}=600V$<br>$V_{GE}=\pm 15V$<br>$R_G=1.3\Omega$<br>$T_{vj}=25^{\circ}C$  |       | 151  |      | ns       |
| Rise Time                               | $t_r$         |                                                                                             |       | 88   |      | ns       |
| Turn-off Delay Time                     | $t_{d(off)}$  |                                                                                             |       | 302  |      | ns       |
| Fall Time                               | $t_f$         |                                                                                             |       | 172  |      | ns       |
| Energy Dissipation During Turn-on Time  | $E_{on}$      |                                                                                             |       | 46.9 |      | mJ       |
| Energy Dissipation During Turn-off Time | $E_{off}$     |                                                                                             |       | 33.2 |      | mJ       |
| Turn-on Delay Time                      | $t_{d(on)}$   | $I_C=450A$<br>$V_{CE}=600V$<br>$V_{GE}=\pm 15V$<br>$R_G=1.3\Omega$<br>$T_{vj}=150^{\circ}C$ |       | 160  |      | ns       |
| Rise Time                               | $t_r$         |                                                                                             |       | 97   |      | ns       |
| Turn-off Delay Time                     | $t_{d(off)}$  |                                                                                             |       | 349  |      | ns       |
| Fall Time                               | $t_f$         |                                                                                             |       | 234  |      | ns       |
| Energy Dissipation During Turn-on Time  | $E_{on}$      |                                                                                             |       | 67.4 |      | mJ       |
| Energy Dissipation During Turn-off Time | $E_{off}$     |                                                                                             |       | 40.4 |      | mJ       |
| SC Data                                 | $I_{sc}$      | $t_p \leq 10\mu s, V_{GE}=15V, T_{vj}=150^{\circ}C, V_{CC}=900V, V_{CEM} \leq 1200V$        |       | 2250 |      | A        |

## ● Diode

### Absolute Maximum Ratings

| Parameter                       | Symbol    | Conditions                              | Value | Unit             |
|---------------------------------|-----------|-----------------------------------------|-------|------------------|
| Repetitive Peak Reverse Voltage | $V_{RRM}$ | $T_{vj}=25^{\circ}C$                    | 1200  | V                |
| Continuous DC Forward Current   | $I_F$     |                                         | 450   | A                |
| Repetitive Peak Forward Current | $I_{FRM}$ | $t_p=1ms$                               | 900   | A                |
| $I^2t$ -value                   | $I^2t$    | $V_R=0V, t_p=10ms, T_{vj}=125^{\circ}C$ | 32000 | A <sup>2</sup> s |
|                                 |           | $V_R=0V, t_p=10ms, T_{vj}=150^{\circ}C$ | 30000 |                  |

### Characteristic Values

| Parameter                     | Symbol    | Conditions                                   | Value |      |      | Unit |
|-------------------------------|-----------|----------------------------------------------|-------|------|------|------|
|                               |           |                                              | Min.  | Typ. | Max. |      |
| Forward Voltage               | $V_F$     | $I_F=450A, T_{vj}=25^{\circ}C$               |       | 1.90 |      | V    |
|                               |           | $I_F=450A, T_{vj}=125^{\circ}C$              |       | 1.80 |      |      |
|                               |           | $I_F=450A, T_{vj}=150^{\circ}C$              |       | 1.75 |      |      |
| Recovered Charge              | $Q_{rr}$  | $I_F=450A$                                   |       | 21.6 |      | uC   |
| Peak Reverse Recovery Current | $I_{rr}$  | $V_R=600V$                                   |       | 156  |      | A    |
| Reverse Recovery Energy       | $E_{rec}$ | $-di_F/dt=3600A/us$<br>$T_{vj}=25^{\circ}C$  |       | 6.52 |      | mJ   |
| Recovered Charge              | $Q_{rr}$  | $I_F=450A$                                   |       | 61.2 |      | uC   |
| Peak Reverse Recovery Current | $I_{rr}$  | $V_R=600V$                                   |       | 257  |      | A    |
| Reverse Recovery Energy       | $E_{rec}$ | $-di_F/dt=3600A/us$<br>$T_{vj}=150^{\circ}C$ |       | 21.2 |      | mJ   |

## ● NTC-Thermistor

### Characteristic values

| Parameter         | Symbol       | Conditions                                     | Value |      |      | Unit |
|-------------------|--------------|------------------------------------------------|-------|------|------|------|
|                   |              |                                                | Min.  | Typ. | Max. |      |
| Rated Resistance  | $R_{25}$     |                                                |       | 5.0  |      | kΩ   |
| Deviation of R100 | $\Delta R/R$ | $T_C=100, R_{100}=493.3\Omega$                 | -5    |      | 5    | %    |
| Power Dissipation | $P_{25}$     |                                                |       |      | 20.0 | mW   |
| B-value           | $B_{25/50}$  | $R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298.15K))]$ |       | 3375 |      | K    |





## ● Module Characteristics





$T_C=25^{\circ}C$  unless otherwise specified




| Parameter | Symbol | Conditions | Value | Unit |
|-----------|--------|------------|-------|------|
|-----------|--------|------------|-------|------|

# MG450HF12TLE3


|                                        |                 |                           | Min. | Typ.  | Max.  |     |
|----------------------------------------|-----------------|---------------------------|------|-------|-------|-----|
| Isolation voltage                      | $V_{isol}$      | $t=1min, f=50Hz$          | 2500 |       |       | V   |
| Maximum Junction Temperature           | $T_{jmax}$      |                           |      |       | 175   | °C  |
| Operating Junction Temperature         | $T_{vj op}$     |                           | -40  |       | 150   | °C  |
| Storage Temperature                    | $T_{stg}$       |                           | -40  |       | 125   | °C  |
| Thermal Resistance<br>Junction-to Case | $R_{\theta JC}$ | per IGBT                  |      |       | 0.065 | K/W |
|                                        |                 | per Diode                 |      |       | 0.13  |     |
| Thermal Resistance<br>Case-to Sink     | $R_{\theta CS}$ | Conductive grease applied |      | 0.009 |       | K/W |
| Comparative Tracking Index             | CTI             |                           | 200  |       |       |     |
| Module Electrodes Torque               | $M_t$           | Recommended(M6)           | 4.0  |       | 5.0   | N·m |
| Module-to-Sink Torque                  | $M_s$           | Recommended(M5)           | 3.0  |       | 6.0   | N·m |
| Weight of Module                       | G               |                           |      | 345   |       | g   |








## ● Circuit Diagram



## ● Package Outline Information



## Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.