




N-Channel Enhancement Mode Field Effect Transistor



PDFN5060-8L



Product Summary

- V_{DS} 60V
- I_D 30A
- $R_{DS(ON)}$ (at $V_{GS}=10V$) $<20m\Omega$
- $R_{DS(ON)}$ (at $V_{GS}=4.5V$) $<23m\Omega$
- 100% EAS Tested
- 100% ∇V_{DS} Tested

General Description

- Trench Power MV MOSFET technology
- High density cell design for LOW $R_{DS(ON)}$
- High Speed switching
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

Applications

- DC-DC Converters
- Power management functions
- Backlighting

■ Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-source Voltage	V_{DS}	60	V
Gate-source Voltage	V_{GS}	± 20	V
Drain Current	I_D	$T_C=25^\circ\text{C}$ 30	A
		$T_C=100^\circ\text{C}$ 19	
Pulsed Drain Current ^A	I_{DM}	130	A
Total Power Dissipation @ $T_C=25^\circ\text{C}$	P_D	45	W
Single Pulse Avalanche Energy ^B	E_{AS}	100	mJ
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	2.8	$^\circ\text{C}/\text{W}$
Junction and Storage Temperature Range	T_J, T_{STG}	-55~+150	$^\circ\text{C}$

■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SCG30N06A	F1	SCG30N06A	5000	10000	100000	13" reel

SCG30N06A

■ Electrical Characteristics (T_J=25℃ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} = 0V, I _D =250μA	60			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =60V,V _{GS} =0V			1	μA
Gate-Body Leakage Current	I _{GSS}	V _{GS} = ± 20V, V _{DS} =0V			±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D =250μA	1.0	1.5	2.5	V
Static Drain-Source On-Resistance	R _{DS(ON)}	V _{GS} = 10V, I _D =15A		16	20	mΩ
		V _{GS} = 4.5V, I _D =10A		17.5	23	
Diode Forward Voltage	V _{SD}	I _S =10A,V _{GS} =0V		0.85	1.2	V
Maximum Body-Diode Continuous Current	I _S				30	A
Dynamic Parameters						
Input Capacitance	C _{iss}	V _{DS} =30V,V _{GS} =0V,f=1MHZ		2027		pF
Output Capacitance	C _{oss}			132		
Reverse Transfer Capacitance	C _{rss}			116		
Switching Parameters						
Total Gate Charge	Q _g	V _{GS} =10V,V _{DS} =30V,I _D =10A		51		nC
Gate-Source Charge	Q _{gs}			8.1		
Gate-Drain Charge	Q _{gd}			11.4		
Reverse Recovery Charge	Q _{rr}	I _F =20A, di/dt=500A/us		11.4		
Reverse Recovery Time	t _{rr}			22		
Turn-on Delay Time	t _{D(on)}	V _{GS} =10V, V _{DD} =30V, I _D =2A, R _{GEN} =3Ω		11		ns
Turn-on Rise Time	t _r			21		
Turn-off Delay Time	t _{D(off)}			40		
Turn-off fall Time	t _f			23		

A. Pulse Test: Pulse Width≤300us,Duty cycle ≤2%.

B. R_{θJA} is the sum of the junction-to-case and case-to-ambient thermal resistance, where the case thermal reference is defined as the solder mounting surface of the drain pins. R_{θJC} is guaranteed by design, while R_{θJA} is determined by the board design. The maximum rating presented here is based on mounting on a 1 in 2 pad of 2oz copper.

■ Typical Performance Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance vs. Junction Temperature




Figure 5. Capacitance Characteristics




Figure 6. Gate Charge




Figure 7. Safe Operation Area




Figure 8. Maximum Continuous Drain Current vs Case Temperature










Figure 9. Normalized Maximum Transient Thermal Impedance





Resistive Switching Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms




Gate Charge Test Circuit & Waveform




Unclamped Inductive Switching (UIS) Test Circuit & Waveforms


■ PDFN5060-8L-B-1.1MM Package Information




Top View
正面视图



Bottom View
背面视图



Side View
侧面视图



Suggested Solder Pad Layout
Top View

SYMBOL	MILLIMETER		
	MIN	NOM	MAX
D	5.15	5.35	5.55
E	5.95	6.15	6.35
A	1.00	1.10	1.20
A1	0.254 BSC		
A2			0.10
D1	3.92	4.12	4.32
E1	3.52	3.72	3.92
D2	5.00	5.20	5.40
E2	5.66	5.86	6.06
E3	0.254 REF		
E4	0.21 REF		
L1	0.56	0.66	0.76
L2	0.50 BSC		
b	0.31	0.41	0.51
e	1.27 BSC		

Note:

- 1.Controlling dimension:in millimeters.
- 2.General tolerance:±0.10mm.
- 3.The pad layout is for reference purposes only.

Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) or consult your nearest Russiansunco's sales office for further assistance.