


P-Channel Enhancement Mode Field Effect Transistor



PDFN5060-8L

Product Summary

- V_{DS} -60V
- I_D -40A
- $R_{DS(ON)}$ (at $V_{GS}=-10V$) <25 mohm
- $R_{DS(ON)}$ (at $V_{GS}=-4.5V$) <30 mohm
- 100% EAS Tested
- 100% ∇V_{DS} Tested

General Description

- Split gate trench MOSFET technology
- Low $R_{DS(ON)}$ & FOM
- Low C_{rss}
- Extremely low switching loss
- Excellent stability and uniformity
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

Applications

- Load Switch
- Industrial DC/DC Conversion Circuits

■ Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-source Voltage		V_{DS}	-60	V
Gate-source Voltage		V_{GS}	± 20	V
Drain Current	$T_C=25^\circ\text{C}$	I_D	-40	A
	$T_C=100^\circ\text{C}$		-25	
Pulsed Drain Current ^A		I_{DM}	-160	A
Avalanche energy ^B		EAS	256	mJ
Total Power Dissipation ^C	$T_C=25^\circ\text{C}$	P_D	88	W
	$T_C=100^\circ\text{C}$		35.2	
Junction and Storage Temperature Range		T_J, T_{STG}	-55~+150	$^\circ\text{C}$

■ Thermal resistance

Parameter		Symbol	Typ	Max	Units
Thermal Resistance Junction-to-Ambient ^D	$t \leq 10S$	$R_{\theta JA}$	15	20	$^\circ\text{C/W}$
Thermal Resistance Junction-to-Ambient ^D	Steady-State		40	50	
Thermal Resistance Junction-to-Case	Steady-State	$R_{\theta JC}$	1.15	1.42	

■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SCG40GP06A	F1	SCG40GP06A	5000	10000	100000	13" reel

SCG40GP06A

■ Electrical Characteristics (T_J=25°C unless otherwise noted)

Parameter	Symbol	Conditions		Min	Typ	Max	Units
Static Parameter							
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} = 0V, I _D =-250μA		-60			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =-60V, V _{GS} =0V	T _J =25℃			-1	μA
			T _J =55℃			-5	
Gate-Body Leakage Current	I _{GSS}	V _{GS} = ±20V, V _{DS} =0V				±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D =-250μA		-1.3	-1.8	-2.5	V
Static Drain-Source On-Resistance	R _{DS(ON)}	V _{GS} = -10V, I _D =-20A			16	25	mΩ
		V _{GS} = -4.5V, I _D =-10A			23	30	
Gate Resistance	R _g	f=1MHz			6		Ω
Diode Forward Voltage	V _{SD}	I _S =-20A, V _{GS} =0V			-0.85	-1.3	V
Maximum Body-Diode Continuous Current	I _S					-40	A
Dynamic Parameters							
Input Capacitance	C _{iss}	V _{DS} =-30V, V _{GS} =0V, f=1MHZ			2200		pF
Output Capacitance	C _{oss}				700		
Reverse Transfer Capacitance	C _{rss}				56		
Switching Parameters							
Total Gate Charge	Q _g (-10V)	V _{GS} =-10V, V _{DS} =-30V, I _D =-20A			37.5		nC
Total Gate Charge	Q _g (-4.5V)				17.4		
Gate-Source Charge	Q _{gs}				8.8		
Gate-Drain Charge	Q _{gd}				7.1		
Reverse Recovery Chrage	Q _{rr}	I _F =-20A, di/dt=100A/us			22.3		ns
Reverse Recovery Time	t _{rr}				33.2		
Turn-on Delay Time	t _{D(on)}	V _{GS} =-10V, V _{DD} =-30V, R _L =2.5Ω R _{GEN} =6Ω			9.9		
Turn-on Rise Time	t _r				39.2		
Turn-off Delay Time	t _{D(off)}				72.5		
Turn-off fall Time	t _f				64.7		

A. Repetitive rating; pulse width limited by max. junction temperature.

B. V_{DD}=50V, R_G=25Ω, L=2mH, I_{AS}=16A.

C. Pd is based on max. junction temperature, using junction-case thermal resistance.

D. The value of R_{qJA} is measured with the device mounted on 1in2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The Power dissipation PDSM is based on R_{qJA} ≤ 10s and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.

■ Typical Performance Characteristics




Figure1. Output Characteristics




Figure2. Transfer Characteristics




Figure3. Capacitance Characteristics




Figure4. Gate Charge




Figure5. : On-Resistance vs. Gate to Source Voltage




Figure6. Normalized On-Resistance




Figure7. Normalized Gate Threshold Voltage




Figure8.Safe Operation Area






Figure9.Normalized Maximum Transient thermal impedance


■ PDFN5060-8L-B-1.1MM Package information




Top View
正面视图



Bottom View
背面视图



Side View
侧面视图



Suggested Solder Pad Layout
Top View

SYMBOL	MILLIMETER		
	MIN	NOM	MAX
D	5.15	5.35	5.55
E	5.95	6.15	6.35
A	1.00	1.10	1.20
A1	0.254 BSC		
A2			0.10
D1	3.92	4.12	4.32
E1	3.52	3.72	3.92
D2	5.00	5.20	5.40
E2	5.66	5.86	6.06
E3	0.254 REF		
E4	0.21 REF		
L1	0.56	0.66	0.76
L2	0.50 BSC		
b	0.31	0.41	0.51
e	1.27 BSC		

Note:

1. Controlling dimension: in millimeters.
2. General tolerance: ± 0.10 mm.
3. The pad layout is for reference purposes only.

Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) or consult your nearest Russiansunco's sales office for further assistance.