


P-Channel Enhancement Mode Field Effect Transistor



Product Summary

• V_{DS}	-100V
• I_D	-0.8A
• $R_{DS(ON)}$ (at $V_{GS}=-10V$)	<600mΩ
• $R_{DS(ON)}$ (at $V_{GS}=-4.5V$)	<650mΩ

General Description

- Voltage controlled small signal switch
- Fast Switching Speed
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

Applications

- Power Management Functions
- Motor Control
- DC-DC convertor

■ Absolute Maximum Ratings ($T_J=25^{\circ}C$ unless otherwise noted)

Parameter			Symbol	Limit	Unit
Drain-source Voltage			V _{DS}	-100	V
Gate-source Voltage			V _{GS}	±20	V
Continuous Drain Current (Note 1,2)	Steady-State	T _A =25°C	I _D	-0.8	A
		T _A =100°C		-0.5	
Pulsed Drain Current	T _C =25°C, t _p =100μs		I _{DM}	-6.4	A
Total Power Dissipation (Note 1,2)	Steady-State	T _A =25°C	P _D	1	W
		T _A =100°C		0.4	
Junction and Storage Temperature Range			T _J , T _{STG}	-55~+150	°C

■ Thermal resistance

Parameter		Symbol	Typ	Max	Units
Thermal Resistance Junction-to-Ambient (Note 2)	Steady-State	$R_{\theta JA}$	105	125	$^{\circ}C/W$

■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SCL600P10AJ	F2	600P10	3000	30000	120000	7" reel

■ Electrical Characteristics (T_J=25°C unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} = 0V, I _D =-250μA	-100	-	-	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =-100V, V _{GS} =0V	-	-	-1	μA
		V _{DS} =-100V, V _{GS} =0V, T _j =150°C	-	-	-100	
Gate-Body Leakage Current	I _{GSS}	V _{GS} = ±20V, V _{DS} =0V	-	-	±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D =-250μA	-1.2	-1.7	-2.2	V
Static Drain-Source On-Resistance	R _{DS(on)}	V _{GS} =-10V, I _D =-0.8A	-	440	600	mΩ
		V _{GS} =-4.5V, I _D =-0.8A	-	480	650	
Diode Forward Voltage	V _{SD}	I _S =-0.8A, V _{GS} =0V	-	-	-1.2	V
Gate resistance	R _G	f=1MHz	-	22	-	Ω
Maximum Body-Diode Continuous Current	I _S		-	-	-0.8	A
Dynamic Parameters						
Input Capacitance	C _{iss}	V _{DS} =-50V, V _{GS} =0V, f=1MHz	-	500	-	pF
Output Capacitance	C _{oss}		-	13.3	-	
Reverse Transfer Capacitance	C _{rss}		-	10.4	-	
Switching Parameters						
Total Gate Charge	Q _g	V _{GS} =-10V, V _{DS} =-50V, I _D =-3A	-	9.5	-	nC
Gate-Source Charge	Q _{gs}		-	0.7	-	
Gate-Drain Charge	Q _{gd}		-	1.6	-	
Reverse Recovery Charge	Q _{rr}	I _F =-3A, di/dt=100A/us	-	35	-	nC
Reverse Recovery Time	t _{rr}		-	24	-	ns
Turn-on Delay Time	t _{D(on)}	V _{GS} =-10V, V _{DD} =-50V, I _D =-3A R _{GEN} =2.7Ω	-	4.9	-	ns
Turn-on Rise Time	t _r		-	31.3	-	
Turn-off Delay Time	t _{D(off)}		-	32.9	-	
Turn-off fall Time	t _f		-	34.1	-	

Note:

1. The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted.
2. The value of R_{θJA} is measured with the device mounted on the 40mm*40mm*1.1mm single layer FR-4 PCB board with 1 in² pad of 2oz. Copper, in the still air environment with T_A =25°C. The maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.

■ Typical Electrical and Thermal Characteristics Diagrams




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance Characteristics




Figure 4. Gate Charge




Figure 5. On-Resistance vs Gate to Source Voltage




Figure 6. Normalized On-Resistance




Figure 7. RDS(on) VS Drain Current




Figure 8. Forward characteristics of reverse diode




Figure 9. Normalized breakdown voltage




Figure 10. Normalized Threshold voltage




Figure 11. Current dissipation




Figure 12. Power dissipation




Figure 13. Maximum Transient Thermal Impedance






Figure 14. Safe Operation Area


■ SOT-23 Package information




TOP VIEW



SIDE VIEW



SIDE VIEW



UNIT: mm

SUGGESTED SOLDER PAD LAYOUT

SYMBOL	DIMENSIONS			
	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.045	0.900	1.150
A1	0.000	0.004	0.000	0.100
A2	0.035	0.041	0.900	1.050
b	0.012	0.020	0.300	0.500
c	0.004	0.008	0.100	0.200
D	0.110	0.118	2.800	3.000
E	0.047	0.055	1.200	1.400
E1	0.089	0.100	2.250	2.550
e	0.037 TYP		0.950 TYP	
e1	0.071	0.079	1.800	2.000
L	0.022 REF		0.550 REF	
L1	0.012	0.020	0.300	0.500
θ	0°	8°	0°	8°

NOTE:
 1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
 2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
 3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.

Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.russiansunco.co> or consult your nearest Russiansunco's sales office for further assistance.