


## 4-Line, Uni-directional, Ultra-low Capacitance, Transient Voltage Suppressor



### Features

- 65W peak pulse power (8/20 $\mu$ s)
- Ultra low leakage
- Operating voltage: 5.0V
- Low clamping voltage
- Up to 4 lines protects
- Compliant

### Applications

- HDMI1.3 /1.4/2.0, USB 2.0/3.0 Type C
- Monitors and flat panel displays
- Set-top box and Digital TV
- MDDI ports
- Video graphics cards
- Digital Video Interface (DVI)
- Notebook Computers
- PCI Express and Serial SATA Ports


### Mechanical Data

- Package: DFN2510-10 (2.5×1.0×0.5mm)
- Terminals: Tin plated leads, solderabl per J-STD-002 and JESD22-B102
- Polarity: Cathode line denotes the cathode end
- Marking:



0524L: Device Marking Code  
Dot denotes Pin1

### ■Definitions of electrical characteristics



**■Maximum Ratings**

| PARAMETER                                       | SYMBOL    | LIMITS   | UNIT        |
|-------------------------------------------------|-----------|----------|-------------|
| Peak pulse power ( $t_p = 8/20\mu s$ )          | $P_{pk}$  | 65       | W           |
| Peak pulse current ( $t_p = 8/20\mu s$ )        | $I_{PP}$  | 8        | A           |
| ESD according to IEC61000-4-2 air discharge     | $V_{ESD}$ | $\pm 15$ | KV          |
| ESD according to IEC61000-4-2 contact discharge |           | $\pm 15$ |             |
| Junction temperature                            | $T_J$     | 125      | $^{\circ}C$ |
| Operating temperature                           | $T_{OP}$  | -55~150  | $^{\circ}C$ |
| Storage temperature                             | $T_{STG}$ | -55~150  | $^{\circ}C$ |

**■Electrical Characteristics** ( $T_a=25^{\circ}C$  Unless otherwise specified)

| PARAMETER                       | Symbol     | UNIT | Conditions                                    | Min | Typ  | Max |
|---------------------------------|------------|------|-----------------------------------------------|-----|------|-----|
| Reverse maximum working voltage | $V_{RWM}$  | V    | Any I/O pin to ground                         |     |      | 5   |
| Reverse leakage current         | $I_R$      | nA   | $V_{RWM} = 5V$ ,<br>any I/O pin to ground     |     |      | 200 |
| Reverse breakdown voltage       | $V_{(BR)}$ | V    | $I_T = 1mA$ ,<br>any I/O pin to ground        | 5.8 | 7.4  | 9.5 |
| Reverse holding voltage         | $V_{HOLD}$ | V    | $I_{HOLD} = 50mA$ ,<br>any I/O pin to ground  | 1   |      |     |
| Clamping voltage <sup>1)</sup>  | $V_{CL}$   | V    | $I_{PP} = 16A$ , $t_p = 100ns$                |     | 9    |     |
| Clamping voltage <sup>3)</sup>  | $V_{CL}$   | V    | $I_{PP} = 1A$ , $t_p = 8/20\mu s$             |     |      | 6   |
|                                 |            | V    | $I_{PP} = 8A$ , $t_p = 8/20\mu s$             | 4   |      | 7   |
| Junction capacitance            | CJ         | pF   | $V_R = 0V$ , $f = 1MHz$<br>Any I/O pin to GND |     | 0.7  | 1.0 |
|                                 |            |      | $V_R = 2V$ , $f = 1MHz$<br>Any I/O pin to GND |     | 0.45 | 0.6 |

Notes:

1) TLP parameter:  $Z_0 = 50\Omega$ ,  $t_p = 100ns$ ,  $t_r = 2ns$ , averaging window from 60ns to 80ns.

2) Contact discharge mode, according to IEC61000-4-2.

**■Ordering Information (Example)**

| PREFERED P/N | PACKING CODE | UNIT WEIGHT(mg)  | MINIMUM PACKAGE(pcs) | INNER BOX QUANTITY(pcs) | OUTER CARTON QUANTITY(pcs) | DELIVERY MODE |
|--------------|--------------|------------------|----------------------|-------------------------|----------------------------|---------------|
| 0524PL       | F1           | Approximate 3.48 | 3000                 | 30000                   | 120000                     | 7 reel        |

## ■ Characteristics (Typical)

Fig.1 8/20 $\mu$ s waveform per IEC61000-4-5




Fig.2 Contact discharge current waveform per IEC61000-4-2




Fig.3 Clamping voltage vs. Peak pulse current




Fig.4 Capacitance vs. Reverse voltage




Fig.5 Non-repetitive peak pulse power vs. Pulse time




Fig.6 Power derating vs. Ambient temperature








Fig.7 TLP Measurement




## Outline Dimensions



| SYMBOL | MILLIMETER |      |      |
|--------|------------|------|------|
|        | MIN        | NOM  | MAX  |
| A      | 0.40       | 0.45 | 0.50 |
| A1     | --         | 0.02 | 0.05 |
| B      | 0.15       | 0.20 | 0.25 |
| B1     | 0.35       | 0.40 | 0.45 |
| C      | 0.10       | 0.15 | 0.20 |
| D      | 2.45       | 2.50 | 2.55 |
| E      | 0.95       | 1.00 | 1.05 |
| F      | 0.50 BSC   |      |      |
| G      | 2.00 BSC   |      |      |
| H      | 0.30       | 0.38 | 0.46 |
| R      | 0.125 BSC  |      |      |
| J      | 0.10       | 0.15 | 0.20 |

## Soldering Footprint



| SYM | DIMENSIONS  |        |
|-----|-------------|--------|
|     | MILLIMETERS | INCHES |
| X1  | 0.200       | 0.008  |
| X2  | 0.400       | 0.016  |
| X3  | 0.600       | 0.024  |
| Y   | 0.600       | 0.024  |
| Z   | 1.400       | 0.056  |

### Notes:

This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met.

**Disclaimer**

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.