


2-Line, Uni-directional, Transient Voltage Suppressor



Features


- Stand-off voltage: 5V Max
- Transient protection for each line according to
 - IEC61000-4-2(ESD): 20kV (contact)
 - IEC61000-4-5(surge): 5A (8/20μs)
- Low leakage current:
- Ultra low clamping voltage
- Compliant

Applications


- Mobile Display Digital Interface (MDDI)
- USB 2.0
- Portable Instrumentation
- HBT Power Amplifier Protection
- Infiniband Transceiver Protection
- Firewire Ports

Mechanical Data

- Package: SOT-523
- Lead Finish: Matte Tin
- Case Material: "Green" Molding Compound
- Marking Information: See Below



■Definitions of electrical characteristics



■Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power ($t_p = 8/20\mu s$)	P_{pk}	80	W
Peak pulse current ($t_p = 8/20\mu s$)	I_{pp}	5	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 25	KV
ESD according to IEC61000-4-2 contact discharge		± 20	
Junction temperature	T_J	-55~150	$^{\circ}C$
Storage temperature	T_{STG}	-55~150	$^{\circ}C$

■Electrical Characteristics ($T_a=25^{\circ}C$ Unless otherwise specified)

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V	pin1 or pin2 to pin3 and between pin1 and pin 2			5
Reverse leakage current	I_R	μA	$V_{RWM} = 5V$, pin1 or pin2 to pin 3 and between pin 1 and pin 2			0.5
Reverse breakdown voltage	V_{BR}	V	$I_T = 1mA$, pin 1 or pin 2 to pin 3	6		
Clamping voltage ¹⁾	V_{CL}	V	$I_{PP} = 1A$, $t_p = 8/20\mu s$, pin 1 pin 2			9
		V	$I_{PP} = 5A$, $t_p = 8/20\mu s$, pin 1 or pin 2 to pin 3			16
Junction capacitance	C_J	pF	$V_R = 0V$, $f = 1MHz$, pin 1 to pin 2		0.3	
Junction capacitance	C_J	pF	$V_R = 0V$, $f = 1MHz$, pin 1 or pin 2 to pin 3		0.6	0.8

Notes:

(1). Non-repetitive current pulse, according to IEC61000-4-5.

■Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ESDSL0502S5	F1	Approximate 2.7	3000	30000	120000	7" reel

■ Characteristics (Typical)

Fig.1 8/20μs waveform per IEC61000-4-5




Fig.2 Contact discharge current waveform per IEC61000-4-2




Fig.3 Clamping voltage vs. Peak pulse current




Fig.4 Capacitance vs. Reverse voltage




Fig.5 Non-repetitive peak pulse power vs. Pulse time




Fig.6 Power derating vs. Ambient temperature




Fig.7 ESD clamping - I/O to GND
(+8kV contact discharge per IEC61000-4-2)









Fig.8 TLP Measurement




■ Outline Dimensions



DIMENSIONS						
DIM	INCHES			MILLIMETERS		
	MIN	NOM	MAX	MIN	NOM	MAX
A	.023	-	.035	0.60	-	0.90
A1	.000	-	.004	0.00	-	0.10
A2	.023	.030	.031	0.60	0.75	0.80
b	.005	-	.012	0.15	-	0.30
c	.003	-	.008	0.10	-	0.20
D	.059	.063	.067	1.50	1.60	1.70
E	.057	.063	.069	1.45	1.60	1.75
E1	.029	.031	.033	0.75	0.80	0.85
e	.039 BSC			1.00 BSC		
e1	.020 BSC			0.50 BSC		
L	(.009)			(0.22)		
N	3			3		
θ	0°	-	8°	0°	-	8°
aaa	.004			0.10		
bbb	.008			0.20		



■ Soldering Footprint



SYM	DIMENSIONS	
	INCHES	MILLIMETERS
C	(.055)	(1.40)
P	.039	1.00
P1	.020	0.50
G	.024	0.60
X	.016	0.40
Y	.031	0.80
Z	.087	2.20

Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.