


2-Line, Asymmetrical, Transient Voltage Suppressor



Features

- Stand-off voltage: 7V or 12V
- Transient protection for each line according to
IEC61000-4-2(ESD): $\pm 30\text{kV}$ (contact)
IEC61000-4-5(surge): 17A or 12A (8/20 μs)
- Low leakage current:
- Ultra low clamping voltage
- Compliant

Applications


- Wireless System
- Networks
- Portable Instrumentation
- RS485 Ports

Mechanical Data

- Package: SOT-23
- Lead Finish: Matte Tin
- Case Material: "Green" Molding Compound
- Moisture Sensitivity: Level 1 per J-STD-020
- Marking Information: See Below



■ Definitions of electrical characteristics



■Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power ($t_p = 8/20\mu s$)	P_{pk}	240	W
Peak pulse current ($t_p = 8/20\mu s$), Pin 1,2 to Pin 3	I_{PP}	12	A
Peak pulse current ($t_p = 8/20\mu s$), Pin 3 to Pin 1,2	I_{PP}	17	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 30	KV
ESD according to IEC61000-4-2 contact discharge		± 30	
Junction temperature	T_J	-55~125	°C
Storage temperature	T_{STG}	-55~150	°C

■Electrical Characteristics ($T_a=25^\circ C$ Unless otherwise specified)

PARAMETER	Symbol	UNIT	Conditions		Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V	Pin 1,2 to Pin 3				12
			Pin 3 to Pin 1,2				7
Reverse leakage current	I_R	μA	Pin 1,2 to Pin 3	$V_{RWM} = 12V$			0.5
			Pin 3 to Pin 1,2	$V_{RWM} = 7V$			0.5
Reverse breakdown voltage	V_{BR}	V	Pin 1,2 to Pin 3	$I_T = 1mA$	13.3		
			Pin 3 to Pin 1,2	$I_T = 1mA$	7.5		
Clamping voltage ¹⁾	V_{CL}	V	Pin 1,2 to Pin 3	$I_{PP} = 1A, t_p = 8/20\mu s$			17
				$I_{PP} = 12A, t_p = 8/20\mu s$			20
			Pin 3 to Pin 1,2	$I_{PP} = 1A, t_p = 8/20\mu s$			11
				$I_{PP} = 12A, t_p = 8/20\mu s$			13
				$I_{PP} = 17A, t_p = 8/20\mu s$			14.5
Junction capacitance	C_J	pF	Pin 1,2 to Pin 3	$V_R = 0V, f = 1MHz$		25	
				$V_R = V_{RWM}, f = 1MHz$		16	
			Pin 3 to Pin 1,2	$V_R = 0V, f = 1MHz$		25	
				$V_R = V_{RWM}, f = 1MHz$		20	

Notes:

(1). Non-repetitive current pulse, according to IEC61000-4-5.

■Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SM712Y	F2	Approximate 8	3000	30000	120000	7" reel

■ Characteristics (Typical)

Fig.1 8/20 μ s waveform per IEC61000-4-5




Fig.2 Contact discharge current waveform per IEC61000-4-2




Fig.3 Clamping voltage vs. Peak pulse current




Fig.4 Capacitance vs. Reverse voltage




Fig.5 Non-repetitive peak pulse power vs. Pulse time




Fig.6 Power derating vs. Ambient temperature







Fig.7 TLP Measurement




■ Outline Dimensions



Symbol	Dimensions in millimeters		
	Min.	Typ.	Max.
A	0.900	-	1.150
A1	0.000	-	0.100
A2	0.900	-	1.050
b	0.300	-	0.500
c	0.100	-	0.200
D	2.800	-	3.000
E	1.200	-	1.400
E1	2.250	-	2.550
e	0.950TYP		
e1	1.800	-	2.000
L	0.550REF		
L1	0.300	-	0.500
θ	0°	-	8°

■ Soldering Footprint



Unit:mm

Notes:

This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met

Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.