



## Bridge Rectifiers



### Features

- UL recognition, file #E230084
- Glass passivated chip junction
- Ideal for printed circuit boards
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

### Typical Applications

General purpose use in AC/DC bridge full wave rectification for monitor, TV, printer, power supply, switching mode power supply, adapter, audio equipment, and home appliances applications.

### Mechanical Data

- **Package:** GBU  
Molding compound meets UL 94 V-0 flammability rating, -
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

### ■Maximum Ratings (Ta=25°C Unless otherwise specified )

| PARAMETER                                                                        |                              | SYMBOL | UNIT  | GBU6005A   | GBU601A | GBU602A | GBU604A | GBU606A | GBU608A | GBU610A |
|----------------------------------------------------------------------------------|------------------------------|--------|-------|------------|---------|---------|---------|---------|---------|---------|
| Device marking code                                                              |                              |        |       | GBU6005A   | GBU601A | GBU602A | GBU604A | GBU606A | GBU608A | GBU610A |
| Maximum Repetitive Peak Reverse Voltage                                          |                              | VRRM   | V     | 50         | 100     | 200     | 400     | 600     | 800     | 1000    |
| Maximum RMS Voltage                                                              |                              | VRMS   | V     | 35         | 70      | 140     | 280     | 420     | 560     | 700     |
| Maximum DC blocking Voltage                                                      |                              | VDC    | V     | 50         | 100     | 200     | 400     | 600     | 800     | 1000    |
| Average rectified output current<br>@60Hz sine wave, R-load                      | With heatsink<br>Tc =125°C   | IO     | A     | 6.0        |         |         |         |         |         |         |
|                                                                                  | Without heatsink<br>Ta =25°C |        |       | 2.8        |         |         |         |         |         |         |
| Forward Surge Current (Non-repetitive)<br>@60Hz Half-sine wave, 1 cycle, Tj=25°C |                              | IFSM   | A     | 175        |         |         |         |         |         |         |
| Forward Surge Current (Non-repetitive)<br>@1ms, square wave, 1 cycle, Tj=25°C    |                              |        |       | 350        |         |         |         |         |         |         |
| Current squared time<br>@1ms≤t≤8.3ms Tj=25°C, Rating of per diode                |                              | I²t    | A²S   | 127        |         |         |         |         |         |         |
| Storage temperature                                                              |                              | Tstg   | °C    | -55 ~ +150 |         |         |         |         |         |         |
| Junction temperature                                                             |                              | Tj     | °C    | -55 ~ +150 |         |         |         |         |         |         |
| Dielectric strength<br>@ Terminals to case, AC 1 minute                          |                              | Vdis   | KV    | 2.5        |         |         |         |         |         |         |
| Mounting torque<br>@Recommend torque: 5kg·cm                                     |                              | Tor    | kg·cm | 8          |         |         |         |         |         |         |

# GBU6005A THRU GBU610A

## ■Electrical Characteristics (T<sub>a</sub>=25°C Unless otherwise specified)

| PARAMETER                                                         | SYMBOL         | UNIT | TEST CONDITIONS                                           | GBU6005A | GBU601A | GBU602A | GBU604A | GBU606A | GBU608A | GBU610A |
|-------------------------------------------------------------------|----------------|------|-----------------------------------------------------------|----------|---------|---------|---------|---------|---------|---------|
| Maximum instantaneous forward voltage drop per diode              | V <sub>F</sub> | V    | I <sub>FM</sub> =3.0A                                     | 1.0      |         |         |         |         |         |         |
| Maximum DC reverse current at rated DC blocking voltage per diode | I <sub>R</sub> | μA   | T <sub>j</sub> =25°C                                      | 5        |         |         |         |         |         |         |
|                                                                   |                |      | T <sub>j</sub> =125°C                                     | 100      |         |         |         |         |         |         |
| Typical junction capacitance                                      | C <sub>j</sub> | pF   | Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C | 50       |         |         |         |         |         |         |

## ■Thermal Characteristics (T<sub>a</sub>=25°C Unless otherwise specified)



| PARAMETER          |                                                | SYMBOL            | UNIT | GBU6005A | GBU601A | GBU602A | GBU604A | GBU606A | GBU608A | GBU610A |
|--------------------|------------------------------------------------|-------------------|------|----------|---------|---------|---------|---------|---------|---------|
| Thermal Resistance | Between junction and ambient, Without heatsink | R <sub>θJ-A</sub> | °C/W | 25       |         |         |         |         |         |         |
|                    | Between junction and case, With heatsink       | R <sub>θJ-C</sub> |      | 2        |         |         |         |         |         |         |

Note: Device mounted on 75mm x 45mm x 5.5mm Aluminum Plate Heatsink.


## ■Ordering Information (Example)

| PREFERRED P/N         | PACKING CODE | UNIT WEIGHT(g)   | MINIIMUM PACKAGE(pcs) | INNER BOX QUANTITY(pcs) | OUTER CARTON QUANTITY(pcs) | DELIVERY MODE |
|-----------------------|--------------|------------------|-----------------------|-------------------------|----------------------------|---------------|
| GBU6005A THRU GBU610A | B1           | Approximate 3.96 | 20                    | 1000                    | 2000                       | TUBE          |


## ■ Characteristics (Typical)




**FIG3: Typical Forward Voltage**



**FIG4: Typical Reverse Characteristics**



## ■ Outline Dimensions



| GBU |       |       |
|-----|-------|-------|
| Dim | Min   | Max   |
| A   | 21.80 | 22.30 |
| B   | 18.30 | 18.80 |
| C   | 17.50 | 18.00 |
| D   | 3.30  | 3.90  |
| E   | 7.10  | 7.50  |
| F   | 5.50  | 5.90  |
| G   | 1.91  | 2.54  |
| H   | 2.06  | 2.54  |
| I   | 1.02  | 1.27  |
| J   | 4.83  | 5.33  |
| K   | 3.30  | 3.56  |
| L   | 2.40  | 2.66  |
| M   | 0.46  | 0.56  |

### Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.