

MUR120 THRU MUR160

Super Fast Recovery Rectifier




Features

- Ultrafast reverse recovery time
- Low leakage current
- Low switching losses, high efficiency
- High forward surge capability
- Glass passivated chip junction
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

For use in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer and telecommunication.



Mechanical Data

- **Package:** DO-204AL(DO-41)
Molding compound meets UL 94 V-0 flammability rating, -
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Color band denotes the cathode end

■Maximum Ratings (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MUR120	MUR140	MUR160
Device marking code			MUR120	MUR140	MUR160
Maximum Repetitive Peak Reverse Voltage	VRRM	V	200	400	600
Maximum RMS Voltage	VRMS	V	140	280	420
Maximum DC blocking Voltage	VDC	V	200	400	600
Average Forward Current @60Hz sine wave, Resistance load, Ta =75℃	I _{F(AV)}	A	1.0		
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25℃	I _{FSM}	A	35		
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			70		
Current squared time @1ms≤t≤8.3ms Tj=25℃, Rating of per diode	I ² t	A ² s	5		
Typical junction capacitance @Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	Cj	pF	17	16	
Storage Temperature	T _{stg}	℃	-55 ~ +150		
Junction Temperature	T _j	℃	-55 ~ +150		

MUR120 THRU MUR160

■Electrical Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	MUR120	MUR140	MUR160
Maximum instantaneous forward voltage drop per diode	V _F	V	I _{FM} =1.0A	0.875	1.25	
Maximum DC reverse current at rated DC blocking voltage per diode	I _R	μA	T _j =25°C	2.5		
			T _j =125°C	100		
Maximum reverse recovery time	t _{rr}	ns	I _F =0.5A, I _R =1.0A, I _{rr} =0.25A	25	50	

■Dynamic Characteristics

◆ MUR120

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T _{RR}	ns	T _j =25°C	I _F =1A, di/dt=-50A/us V _{RM} =30V	-	26	-
			T _j =25°C	I _F =1A di/dt=-200A/us V _{RM} =100V	-	21	-
			T _j =125°C		-	23	-
Peak recovery current	I _{RRM}	A	T _j =25°C		-	2.6	-
			T _j =125°C		-	3.9	-
Reverse recovery charge	Q _{rr}	nC	T _j =25°C		-	26.8	-
			T _j =125°C		-	44.9	-
Non-repetitive avalanche energy	E _{AS}	mJ	T _j =25°C	I _R =1.6 A, L=15 mH	19.2	-	-

◆ MUR140 THRU MUR160

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T _{RR}	ns	T _j =25°C	I _F =1A, di/dt=-50A/us V _{RM} =30V	-	46	-
			T _j =25°C	I _F =1A di/dt=-200A/us V _{RM} =400V	-	36	-
			T _j =125°C		-	56	-
Peak recovery current	I _{RRM}	A	T _j =25°C		-	3.6	-
			T _j =125°C		-	5.2	-
Reverse recovery charge	Q _{rr}	nC	T _j =25°C		-	63.5	-
			T _j =125°C		-	144.5	-
Non-repetitive avalanche energy	E _{AS}	mJ	T _j =25°C	I _R =1.3A, L=15 mH	12.7	-	-

■Thermal Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MUR120	MUR140	MUR160
Typical Thermal Resistance	R _{θJA}	°C/W	60		

MUR120 THRU MUR160

■ Ordering Information (Example)

PREFERED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MUR120~MUR160	D1	Approximate 0.30	5000	5000	50000	Tape
MUR120~MUR160	C1	Approximate 0.30	1000	1000	50000	Bulk

■ Characteristics(Typical)

FIG.1: Io-Ta Curve




FIG.2: Forward Surge Current Capability




FIG.3: Forward Voltage






FIG.4: Typical Reverse Characteristics




MUR120 THRU MUR160

FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



■ Outline Dimensions



DO-204AL(DO-41)		
Dim	Min	Max
A	4.22	5.21
B	2.03	2.72
C	25.4	/
D	0.69	0.86

Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.