

Surface Mount Super Fast Recovery Rectifier




Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High forward surge capability
- Super Fast reverse recovery time
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

Typical Applications

For use in high frequency rectification of power, supplies, inverters, converters, and freewheeling diodes for consumer, and telecommunication.



Mechanical Data

- **Package:** SMAF
Molding compound meets UL 94 V-0 flammability rating, -compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■Maximum Ratings (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	U2DF
Device marking code			U2DF
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	200
Maximum RMS Voltage	V_{RMS}	V	140
Maximum DC blocking Voltage	V_{DC}	V	200
Average rectified output current @60Hz sine wave, resistance load, TL (Fig.1)	I_O	A	2.0
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, Tj=25°C	I_{FSM}	A	65
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25°C			130
Current squared time @1ms≤t≤8.3ms Tj=25°C	I^2t	A ² s	17.53
Storage temperature	T_{stg}	°C	-55 ~ +175
Junction temperature	T_j	°C	-55 ~ +175

U2DF

■Electrical Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	U2DF
Maximum instantaneous forward voltage	V _F	V	I _{FM} =1.0A	0.93
Maximum reverse recovery time	t _{rr}	ns	I _F =0.5A, I _R =1.0A, I _{rr} =0.25A	25
Maximum DC reverse current at rated DC blocking voltag	I _R	μA	T _j =25°C	5.0
			T _j =125°C	50
Typical junction capacitance	C _j	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	27

■Thermal Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	U2DF
Typical Thermal resistance	R _{θJA} ⁽¹⁾	°C/W	75
	R _{θJL} ⁽¹⁾		25
	R _{θJC} ⁽¹⁾		10

Note:

(1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas

■ Characteristics (Typical)

FIG.1: I_o-T_L Cure




FIG.2: Forward Surge Current Capability




FIG.3: Typical Forward Characteristics




FIG.4: Typical Reverse Characteristics






FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



■Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
U2DF	F1	Approximate 0.034	3000	24000	96000	7" reel
U2DF	F2	Approximate 0.034	10000	/	160000	13" reel
U2DF	F3	Approximate 0.034	10000	/	120000	13" reel
U2DF	F4	Approximate 0.034	7500	/	120000	13" reel

■ Outline Dimensions



SMAF		
Dim	Min	Max
A	2.40	2.80
B	1.35	1.45
C	3.40	3.60
D	4.40	4.80
E	1.05	1.25
F	0.50	1.00
G	0.15	0.22

■ Suggested pad layout



SMAF	
Dim	Millimeters
P1	6.50
P2	4.00
P3	1.50
Q1	2.50
Q2	1.70

Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.