


2SC554

NPN General Purpose Amplifier



Features

- Moisture sensitivity level 1
- Halogen free and
- Surface mount package ideally suited for automatic Insertion

Application

- Low saturation voltage
- High speed switching

Mechanical data

- **Package:** SOT-89
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ Maximum Ratings ($T_a=25^{\circ}\text{C}$ Unless otherwise specified)

Item	Symbol	Unit	Conditions	Value
Device marking code				C554
Collector-base voltage	V_{CBO}	V	$I_C=100\mu\text{A}$, $I_E=0$	100
Collector-emitter voltage	V_{CEO}	V	$I_C=1\text{mA}$, $I_B=0$	100
Emitter-base voltage	V_{EBO}	V	$I_E=100\mu\text{A}$, $I_C=0$	6
Collector current	I_C	A		2
Power dissipation	P_D	mW		500
Operation junction temperature	T_J	$^{\circ}\text{C}$		-55 to +150
Storage temperature	T_{STG}	$^{\circ}\text{C}$		-55 to +150

2SC554

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base breakdown voltage	V _{(BR)CBO}	V	I _C =100μA, I _E =0	100		
Collector-emitter breakdown voltage	V _{(BR)CEO}	V	I _C =1mA, I _B =0	100		
Emitter-base breakdown voltage	V _{(BR)EBO}	V	I _E =100μA, I _C =0	6		
Collector-base cut-off current	I _{CBO}	μA	V _{CB} =100V, I _E =0			1
Emitter-base cut-off current	I _{EBO}	μA	V _{EB} =4V, I _C =0			1
DC current gain	h _{FE}		V _{CE} =3V I _C =100mA	82		270
Collector-emitter saturation voltage	V _{CE(sat)}	V	I _C =500mA I _B =25mA			0.2
		V	I _C =1A I _B =50mA			0.3
Collector-base output capacitance	C _{ob}	pF	V _{CB} =10V, I _E =0, f=1MHz		16	

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	R _{θJ-A} ⁽¹⁾	°C/W	250
Thermal resistance, junction-to-case	R _{θJ-C} ⁽¹⁾	°C/W	200

Note:

(1) Device mounted on PCB, single-sided copper, with standard footprint

■ Characteristics

Fig 1: Static Characteristics




Fig 2: DC Current Gain




Fig 3: Collector-emitter saturation voltage




Fig 4: Base-emitter saturation voltage




Fig 5: Base-emitter on voltage






Fig 6: Cob/Cib- V_{CB}/V_{EB}



2SC554

Fig 7: P_D - T_a Curve




2SC554

■ Ordering Information


Prefered P/N	Packing code	Unit weight(g)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity(pcs)	Delivery mode
2SC554	F2	Approximate 0.055	1000	8000	32000	7" reel

■ Outline Dimensions



DIM	DIMENSIONS			
	INCHES		MM	
	MIN.	MAX.	MIN.	MAX.
A	0.173	0.181	4.400	4.600
B	0.061 TYP.		1.550 TYP.	
C	0.155	0.167	3.940	4.250
D	0.031	0.047	0.800	1.200
E	0.094	0.102	2.400	2.600
F	0.118 TYP.		3.00 TYP.	
G	0.014	0.019	0.360	0.480
H	0.017	0.022	0.440	0.560
J	0.014	0.017	0.350	0.440
K	0.055	0.063	1.400	1.600
L	0.059 TYP.		1.500 TYP.	
M	0.108 TYP.		2.750 TYP.	

■ Suggested Pad Layout



UNIT:MM

2SC554

Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.