


PNP Transistor



Features

- Epoxy meets UL-94 V-0 flammability rating
- Halogen free available upon request by adding suffix "HF"
- Moisture Sensitivity Level 1
- High Conductance
- Surface Mount Package Ideally Suited for Automatic Insertion

Mechanical Data

- **Package:** SOT-323

Molding compound meets UL 94 V-0 flammability rating, -compliant, halogen-free

- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

- **Marking:**

BC856AW	3A
BC856BW	3B
BC857AW	3E
BC857BW	3F
BC857CW	3G
BC858AW	3J
BC858BW	3K
BC858CW	3L

■ Maximum Ratings (Ta=25°C unless otherwise noted)

Symbol	Parameter	Value	Unit
VCBO	Collector-Base Voltage BC856AW、BC856BW BC857AW、BC857BW、BC857CW BC858AW、BC858BW、BC858CW	-80 -50 -30	V
VCEO	Collector-Emitter Voltage BC856AW、BC856BW BC857AW、BC857BW、BC857CW BC858AW、BC858BW、BC858CW	-65 -45 -30	V
VEBO	Emitter-Base Voltage	-6	V
IC	Collector Current	-0.1	A
PC	Collector Power Dissipation	200	mW
RθJA	Thermal Resistance From Junction To Ambient	625	°C/W
Tj	Junction Temperature	150	°C
Tstg	Storage Temperature	-55~+150	°C

BC856AW THRU BC858CW







■ Electrical Characteristics (Ta=25°C unless otherwise noted)

Parameter	Symbol	Test conditions	Min	Max	Unit
Collector-base breakdown voltage BC856 BC857 BC858	V _{CBO}	IC= -10μA, IE=0	-80 -50 -30		V
Collector-emitter breakdown voltage BC856 BC857 BC858	V _{CEO}	IC= -10mA, IB=0	-65 -45 -30		V
Emitter-base breakdown voltage	V _{EBO}	IE= -1μA, IC=0	-5		V
Collector-base cut-off current	I _{CBO}	VCB=-30 V ,IE=0		-0.1	μ A
Emitter-base cut-off current	I _{EBO}	VEB=-5 V , IC=0		-0.1	μ A
DC current gain BC856AW,BC857AW,BC858AW BC856BW,BC857BW,BC858BW BC857CW,BC858CW	h _{FE}	VCE= -5V, IC= -2mA	125 220 420	250 475 800	
Collector-emitter saturation voltage	V _{CE(sat)}	IC=-100mA, IB= -5mA		-0.65	V
Base-emitter saturation voltage	V _{BE(sat)}	IC=-100mA, IB= -5mA		-1.1	V
Transition frequency	f _T	VCE= -5 V, IC= -10mA f=100MHz	100		MHz
Collector-base output capacitance	C _{ob}	VCB=-10V,f=1MHz		4.5	pF

■ Ordering Information (Example)


PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
BC856AW THRU BC858CW	F2	Approximate 0.005	3000	30000	120000	7" reel

■ Characteristics(Typical)




BC856AW THRU BC858CW

■ SOT-323 Package Outline Dimensions



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.071	.087	1.80	2.20	
B	.045	.053	1.15	1.35	
C	.083	.096	2.10	2.45	
D	.026 Nominal		0.65Nominal		
E	.047	.055	1.20	1.40	
F	.012	.016	.30	.40	
G	.000	.004	.000	.100	
H	.035	.039	.90	1.00	
J	.004	.010	.100	.250	
K	.006	.016	.15	.40	

■ SOT-323 Soldering Footprint



Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.