




DTA114EM

PNP Digital Transistors (Built-in Resistors)



1. IN
2. GND
3. OUT

SOT-723

Features

- Moisture sensitivity level 1
- Halogen free and
- Surface mount package ideally suited for automatic insertion.

Application

- Signal amplification
- Switching circuit

Mechanical data

- **Package:** SOT-723
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ Maximum Ratings ($T_a=25^{\circ}\text{C}$ Unless otherwise specified)

Item	Symbol	Unit	Conditions	Value
Device marking code				14
Supply voltage	V_{CC}	V		-50
Input voltage	V_{IN}	V		-40 to 10
Output current	I_O	mA		-100
Power dissipation	P_D	mW		100
Junction temperature	T_J	$^{\circ}\text{C}$		-55 to +150
Storage temperature	T_{STG}	$^{\circ}\text{C}$		-55 to +150

DTA114EM

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Input voltage	V _{I(off)}	V	V _{CC} =-5V, I _O =-100uA	-0.5		
	V _{I(on)}	V	V _O =-0.3V, I _O =-10mA			-3
Output voltage	V _{O (on)}	V	I _O /I _I =-10mA/-0.5 mA			-0.3
Input current	I _I	mA	V _I =-5V			-0.88
Output current	I _{O(off)}	uA	V _{CC} =-50V, V _I =0			-0.5
DC current gain	G _I		V _O =-5V, I _O =-5mA	30		
Input resistance	R ₁	kΩ		7	10	13
Resistance ratio	R ₂ /R ₁			0.8	1	1.2
Transition frequency	f _T	MHz	V _O =-10V, I _O =-5mA, f=100MHz		250	

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	R _{θJ-A} ⁽¹⁾	°C/W	1250
Thermal resistance, junction-to-case	R _{θJ-C} ⁽¹⁾	°C/W	1000

Note:

(1) Thermal resistance from junction to ambient and from junction to case mounted on P.C.B. with 25.4mm*25.4mm copper pad areas

DTA114EM

■ Characteristics

Fig 1: DC Current Gain Characteristics




Fig 2: Input Voltage (On) Characteristics




Fig 3: Input Voltage (Off) Characteristics




Fig 4: Output Voltage Characteristics





Fig 5: PD-Ta Curve




DTA114EM


■ Ordering Information

Preferred P/N	Packing code	Unit weight(g)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity(pcs)	Delivery mode
DTA114EM	F2	Approximate 0.0013	8000	80000	320000	7" reel


■ Outline Dimensions



TOP VIEW




SIDE VIEW



SIDE VIEW

SYMBOL	DIMENSIONS			
	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.017	0.022	0.430	0.550
A1	0.000	0.002	0.000	0.050
b	0.007	0.011	0.170	0.270
b1	0.011	0.015	0.270	0.370
c	0.003	0.008	0.080	0.200
D	0.045	0.049	1.150	1.250
E	0.045	0.049	1.150	1.250
E1	0.030	0.033	0.750	0.850
e	0.031TYP.		0.800TYP.	
θ	7°REF.		7°REF.	

■ Suggested Pad Layout



DTA114EM

Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.