


PNP Power Transistor



Features

- Epoxy meets UL-94 V-0 flammability rating and halogen free
- Moisture Sensitivity Level 1

Applications

- Designed for general purpose amplifier and low speed switching applications.

Mechanical Data

- Package: TO-252
- Terminals: Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ Maximum Ratings (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Value
Device marking code			MJD32C
Collector-Base Voltage	V_{CBO}	V	-100
Collector-Emitter Voltage	V_{CEO}	V	-100
Emitter-Base Voltage	V_{EBO}	V	-5
Collector Current -Continuous	I_C	A	-3
Total Device Dissipation (*)	P_D	W	1.25
Thermal Resistance, Junction to Ambient Air (*)	R_{thJA}	°C/W	100
Junction Temperature	T_j	°C	-55 to +150
Storage Temperature	T_{STG}	°C	-55 to +150

(*) Device mounted on FR-4 PCB 15 x 17 x 0.8 mm

MJD32C

■ Electrical Characteristics (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base breakdown voltage	V_{CBO}	V	$I_C = -1mA, I_E = 0$	-100		
Collector-emitter breakdown voltage	V_{CEO}	V	$I_C = -30mA, I_B = 0$	-100		
Emitter-base breakdown voltage	V_{EBO}	V	$I_E = -1mA, I_C = 0$	-5		
Collector-base cut-off current	I_{CEO}	uA	$V_{CE} = -60V, I_B = 0$			-50
Collector-base cut-off current	I_{CES}	uA	$V_{CE} = -100V, V_{EB} = 0$			-20
Emitter-base cut-off current	I_{EBO}	mA	$V_{EB} = -5V, I_C = 0$			-1
DC current gain	h_{FE}		$V_{CE} = -4V, I_C = -1A$	25		
			$V_{CE} = -4V, I_C = -3A$	10		75
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	$I_C = -3A, I_B = -0.375A$			-1.2
Base-emitter voltage	V_{BE}	V	$I_C = -3A, V_{CE} = -4V$			-1.8

■ Other Characteristics (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Transition frequency	f_T	MHz	$V_{CE} = -10V, I_C = -0.5A, f = 1KHz$	3		

■ Characteristics(Typical)

Fig 1: Static Characteristics




Fig 2: DC Current Gain




Fig 3: Collector-Emittor Saturation Voltage




Fig 4: Base-Emittor Saturation Voltage




Fig 5: Base-Emittor On Voltage






Fig 6: Cob/Cib-VCB/VEB



■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MJD32C	F1	2500	2500	25000	13"Reel


■ TO-252 Package information



Dimensions in millimeters

TO-252		
Dim	Min	Max
A	6.500	6.700
B	5.100	5.460
C	1.400	1.800
D	6.000	6.200
E	10.000	10.400
F	2.166	2.366
G	0.660	0.860
H	Φ 1.050	Φ 1.350
I	0.460	0.580
J	2.200	2.400
K	0	0.300
L	0.890	2.290
M	2.730	3.080
N	0.430	0.580
O	4.20	4.95
P	5.15	5.45
Q	0	0.2

■ Suggested Pad Layout



Dim	Millimeters
A	11.4
B	6.74
C	6.23
P	4.56
Q1	2.28
Q2	1.52

Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, lifesustaining, or military. Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.