


PNP General Purpose Amplifier



Features

- Epoxy meets UL-94 V-0 flammability rating
- Halogen free available upon request by adding suffix "HF"
- Moisture Sensitivity Level 1
- Marking: K4M

■ Maximum Ratings (Ta=25°C)

Item	Symbol	Unit	Conditions	Value
Collector-Emitter Voltage*	V_{CEO}	V	$I_C = -1.0\text{mA}$, $I_E = 0$	-150
Collector-Base Voltage	V_{CBO}	V	$I_C = -100\mu\text{A}$, $I_E = 0$	-160
Emitter-Base Voltage	V_{EBO}	V	$I_E = -10\mu\text{A}$, $I_C = 0$	-5.0
Collector Current	I_C	mA		-600
Collector Power Dissipation	P_C	mW		200
Operation Junction Temperature	T_j	°C		150
Storage Temperature	T_{stg}	°C		-55 to +150

MMST5401

■Electrical Characteristics (T_a=25°C)

Item	Symbol	Unit	Conditions	Min	Max
Collector-Emitter Voltage	V _{CEO}	V	I _C =-1.0mA, I _B =0	-150	
Collector-Base Voltage	V _{CBO}	V	I _C =-100μA, I _E =0	-160	
Emitter-Base Voltage	V _{EBO}	V	I _E =-10μA, I _C =0	-5	
Collector-Base Cut-off Current	I _{CBO}	nA	V _{CB} =-120Vdc		-50
Emitter-Base Cut-off Current	I _{EB0}	nA	V _{EB} =-3Vdc		-50
DC Current Gain	h _{FE}		I _C =-1.0mA V _{CE} =-5.0Vdc	50	
			I _C =-10mA V _{CE} =-5.0Vdc	60	300
			I _C =-50mA V _{CE} =-5.0Vdc	50	
Collector-Emitter Saturation Voltage	V _{CE(sat)}	V	I _C =-50mA I _B =-5.0mA		-0.5
Base-Emitter Saturation Voltage	V _{BE(sat)}	V	I _C =-50mA I _B =-5.0mA		-1.0







■Small-signal Characteristics (T_a=25°C)

Item	Symbol	Unit	Conditions	Min	Max
Transition frequency	f _T	MHz	I _C =-10mA, V _{CE} =-10Vdc, f=100MHz	100	300


■Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MMST5401	F2	Approximate 0.005	3000	30000	120000	7" reel

■ Characteristics(Typical)




■SOT-323 Package Outline Dimensions



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.071	.087	1.80	2.20	
B	.045	.053	1.15	1.35	
C	.083	.096	2.10	2.45	
D	.026 Nominal		0.65Nominal		
E	.047	.055	1.20	1.40	
F	.012	.016	.30	.40	
G	.000	.004	.000	.100	
H	.035	.039	.90	1.00	
J	.004	.010	.100	.250	
K	.006	.016	.15	.40	

■SOT-323 Soldering Footprint



Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.