


Dual NPN Digital Transistors (Built-in Resistors)




Features

- Epoxy meets UL-94 V-0 flammability rating
- Built-in bias resistors enable the configuration of an inverter circuit without connecting external input resistors
- Surface mount package ideally Suited for Automatic Insertion

Mechanical Data

- **Package:** SOT-363
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** H1

■Equivalent circuit



UMH1N

■Maximum Ratings (Ta=25°C Unless otherwise specified)

ITEM	SYMBOL	UNIT	CONDITIONS	VALUE
Supply Voltage	VCC	V		50
Input Voltage	VIN	V		-10 to +40
Output Current	IO	mA		100
Power Dissipation	PD	mW		150
Junction Temperature (Single)	Tj	°C		150
Storage Temperature	TSTG	°C		-55 to +150

■Electrical Characteristics (Ta=25°C unless otherwise specified)


ITEM	SYMBOL	UNIT	CONDITIONS	MIN	TYP	MAX
Input voltage	VI(off)	V	VCC=5V, Ic=100uA	0.5	-	-
	VI(on)	V	V0=0.2V, Ic=5mA	-	-	3
Output voltage	VO(on)	V	Io /Ii =10mA/0.5 mA	-	-	0.3
Input current	II	mA	VI=5V	-	-	0.36
Output current	IO(off)	uA	VCC=50V, Vi=0	-	-	0.5
DC current gain	GI		Vo=5V, Io =5mA	56	-	-
Input resistance	R ₁	kΩ		15.4	22	28.6
Resistance ratio	R ₂ /R ₁			0.8	1	1.2
Transition frequency	fT	MHz	VCE=10V, IE=5mA, f=100MHz	-	250	-

■ Ordering Information (Example)


PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
UMH1N	F2	Approximate 0.009g	3000	30000	120000	7" reel

■ Characteristics (Typical)


ON Characteristics




OFF Characteristics




$V_{O(ON)}$ — I_O




G_I — I_O




C_O — V_R





P_D — T_a




■SOT-363 Package Outline Dimensions



DIM	DIMENSIONS			
	INCHES		MM	
	MIN	MAX	MIN	MAX
A	0.035	0.043	0.9	1.1
A1	0	0.004	0	0.1
A2	0.035	0.039	0.9	1
b	0.006	0.014	0.15	0.35
c	0.002	0.01	0.05	0.25
D	0.071	0.087	1.8	2.2
E	0.045	0.053	1.15	1.35
E1	0.085	0.096	2.15	2.45
e	0.026Typ		0.65Typ	
e1	0.047	0.055	1.2	1.4
L	0.021Typ		0.525Typ	
L1	0.01	0.018	0.26	0.46
θ	0°		8°	



■SOT-363 Suggested Pad Layout



Unit: mm

Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices). Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.